




**TECH SCORE - FLEX S3**

Réf. : 70720












<b>Suitable for :</b>	Outside
<b>Type :</b>	Ankle shoe
<b>Activity :</b>	Construction / Environment / Electronic Industry, ESD
<b>Upper :</b>	Water resistant full nubuck leather
<b>Lining :</b>	ARTICO® black color, up to the toes, slipper feeling
<b>Tongue :</b>	Bellows tongue in leather, lining ARTICO® and padded with 10mm thick foam
<b>Ankle protection :</b>	ON STEAM® microfibre black color, lining ARTICO® and padded with 10 mm thick foam
<b>Fastening :</b>	Eyelets and round brown polyester laces
<b>Toe cap :</b>	Ultralight and extra wide 200 joules, Composite LIGHT SYSTEM®
<b>Midsole :</b>	Composite FLEX SYSTEM®, anti-magnetic and thermal insulated
<b>Insole :</b>	Thermoformed in active carbon dual density foam, antistatic, ESD and antibacterial FRESH TECH®
<b>Sole :</b>	PU 2D, TECH SOLE® ankle anti-twist system, oil resistant FO, antistatic, HI-CI
<b>Sole pattern :</b>	Multi-purpose cleated indoor/outdoor outsole, well-defined heel, cleated arch, SRC standard
<b>Weight (Kg/pair) :</b>	1.200
<b>Colors :</b>	Light brown and black upper; brown/dark grey outsole
<b>Sizes :</b>	35-48 (2-13)
<b>Standard :</b>	EN ISO 20345:2011 SRC / EN 61340-5-1 / DGUV 112-191
<b>CE certificate of conformity N° :</b>	0075/020/161/08/17/1266 - EXT 13/09/17
<b>Special features :</b>	
<b>Special features 2 :</b>	
<b>Special features 3 :</b>	

**SPECIAL FEATURES**

-  Integral 100% composite (Air System + Light System + Flex System)
-  Water absorption and penetration resistance of upper (WRU)
-  Electro Static Discharge Standard EN 61340-5-1



**G GENERAL FEATURES**

-  Antistatic properties (A)
-  Heel energy absorption (E)
-  Abrasion resistance
-  Crampon sole
-  Heat-insulated sole (HI)
-  Cold-insulated sole (CI)
-  200 joule extra-wide toecap
-  Hyper-ventilated lining
-  Perforation-resistance 1100 N (P)